

borg & overström

CLASSIC



Firmly established as a market favourite, the borg and overström Classic water coolers offer point-of-use technology that's both cost-effective and good looking. Boasting a choice of water options, as well as floor-standing or counter-top versions, the Classic makes widely accessible all the advantages of mains-fed, filtered water.

MAINS-FED WATER COOLERS FOR POINT OF USE

STYLISH DESIGN AND ROBUST CONSTRUCTION

SIMPLE TO USE AND EASY TO MAINTAIN

AVAILABLE AS FLOOR-STANDING OR COUNTER-TOP

A CHOICE OF WATER OPTIONS, INCLUDING HOT, AMBIENT, COLD AND DIRECT-CHILL

borg & overström

CLASSIC



MACHINE TYPE (see key)	●	●	●
COOLING SYSTEM			
Thermostatic Control Regulated	●	●	●
Ice Bank Direct Chill	–	–	●
Stainless Steel Tank	●	●	–
HEATING SYSTEM			
Stainless Steel Tank	–	●	–
Tank Size (litres)	–	2	–
Easy change tank	–	●	–
COLOUR			
Silver	●	●	●
COUNTER-TOP DIMENSIONS			
Model Number	628	628H	DC628
Width (mm)	325	325	325
Depth (mm)	380	380	380
Height (mm)	480	480	480
FLOOR-STANDING DIMENSIONS			
Model Number	698	698H	DC698
Width (mm)	325	325	325
Depth (mm)	370	370	370
Height (mm)	1070	1070	1070
STORAGE BASE DIMENSIONS			
Internal Width (mm)	320	320	320
Internal Depth (mm)	245	245	245
Internal Height (mm)	550	550	550
POWER REQUIREMENTS			
Hertz	50	50	50
Volts	220-240	220-240	220-240
MAX POWER CONSUMPTION			
Cold & Ambient (W)	95	95	95
Cold & Hot (W)	–	545	–
COLD TEMPERATURE			
Min °C	4	4	2
Max °C	11	11	11
HOT TEMPERATURE			
Max °C	–	92	–
DISPENSE LEVEL			
Height (mm)	180	180	180
THROUGHPUT LITRES PER HOUR			
Cold	12	12	22
Hot	–	6	–

KEY ● Direct Chill ● Cold ○ Sparkling ● Ambient ● Hot